



Jiangling Bus 10-23 Seats Pure Electric Tourist Bus Model Parameters

Basic Information

. Delivery Time:

Place of Origin: ChinaBrand Name: Fushunte

Model Number: Jiangling Bus (pure electric 10-23 seats)

5-8 work days

tourist bus model parameters

• Minimum Order Quantity: 1 vehicle

Price: \$55,000-\$605000DollarPackaging Details: Complete vehicle

Payment Terms: T/T

• Supply Ability: 1000 vehicle



Product Specification

Accessories: Curtains, Blinds, Fridge, Toilet

• Audio System: Yes

Braking System: Air Brakes
Capacity: 10-23 Seats
Engine: Diesel
Engine Type: Diesel

• Entertainment System: DVD Player, TV Screens

Fuel: DieselInterior: ModernSafety: Seat Belts

• Safety Features: ABS, Airbags, Seatbelts

• Size: Large

• Suspension: Air Suspension

• Toilet: Yes

Windows: Large Viewing Windows



More Images







Product Description

Jiangling Bus (Pure Electric 10-23 Seats) Tourist Bus Model Parameters

Sure! Here's the description of an electric tourist bus:

An electric tourist bus is a specialized vehicle powered by electricity, designed for tourism and sightseeing activities. It utilizes an electric propulsion system, emitting zero tailpipe emissions and operating silently, making it an environmentally friendly and quiet mode of transportation.

The exterior design of an electric tourist bus is typically tailored to meet the requirements of tourism and sightseeing, with a focus on comfort and aesthetics. The vehicle's body structure incorporates lightweight materials to enhance energy efficiency and maximize the driving range. The size and seating capacity of the bus can be customized to accommodate various group sizes and tourism demands.

The bus is equipped with a high-capacity battery pack for energy storage. The battery pack is usually located at the bottom or rear of the vehicle, ensuring balance and efficient space utilization. Charging of the battery pack can be done through external power sources or charging stations, with charging time and driving range depending on the battery technology and capacity. An electric tourist bus is also equipped with advanced electric propulsion and control systems. The electric propulsion system consists of an electric motor, transmission, and drive circuits, delivering efficient power output. The control system monitors and regulates parameters such as battery status, motor output, and energy regeneration to optimize performance and energy utilization.

In terms of passenger experience, an electric tourist bus typically offers spacious and comfortable seating with a well-designed interior layout. The bus is equipped with air conditioning systems and adjustable seats to ensure passenger comfort. Additionally, entertainment facilities such as audio systems, touchscreen displays, and wireless connectivity may be provided to enhance the travel experience.

Safety is a key consideration in the design of an electric tourist bus. It is equipped with safety features such as airbags, anti-lock braking systems, vehicle stability control, and rearview cameras to ensure passenger and driver safety. Emergency cut-off devices and fire suppression equipment may also be installed to handle unforeseen situations.

In summary, an electric tourist bus is an environmentally friendly, quiet, comfortable, and safe mode of transportation for tourism and sightseeing. Its electric propulsion system and advanced control technology offer high energy efficiency and low carbon emissions, aligning with sustainable development trends. By utilizing electric tourist buses, tourism and sightseeing activities can be seamlessly integrated with environmental preservation.

Vehicle parameter configuration:

Purpose: Passenger buses, tourist buses, group buses

Body length: 6640mm Body width: 2280mm Body height: 2840mm Vehicle mass: 5170kg Total mass: 9000kg Number of seats: 20-23 Maximum speed: 100km/h Motor parameters:

Motor type: permanent magnet synchronous motor

Mileage: 310kw

The peak power of the drive motor is: 160kW

Rated power: 80kW Charging time: 1.2 hours

Total battery capacity: 114.52kw.h (v/ah)

Front suspension and rear suspension: 1820/1570mm

Number of spring leaves: 3/4

Number of axes: 2 Wheelbase: 3250mm Axle load: 3500/5500kg Front wheelbase: 1910mm Rear wheelbase: 1600,1640mm Approach departure angle: 13/13° Number of tires: 6 Specifications: 215/75R17.5

Type of energy storage device/manufacturer: lithium iron phosphate battery/CATL New Energy Technology Co., Ltd.

Speed limiter speed limit (km/h): 100;

A driving recorder with satellite positioning function is installed;

The front door is a folding door.

cloth seat











